



A SOLID SUB-COMPACT PERFORMER FOR ANY OPERATION.





20 SERIES



TRACTOR MODEL	2024
TYPE	3 CYLINDER, WATER COOLED, DIESEL
ENGINE HP @ RPM (KW)	24 (17.9)
DISPLACEMENT (IN) (KW)	71.7 (1,175)
NUMBER OF CYLINDERS	3
FUEL TANK (GAL) (L)	6.0 (23)
DRIVE TRAIN	
TRANSMISSION	HST
NUMBER OF SPEEDS	2 RANGE
CLUTCH	DRY SINGLE PLATE
BRAKES	WET, MULTI-DISC
PTO	
TYPE	LIVE
REAR(MID) PTO SPEED	540 / 960 (2,500)
PTO HP (KW)	18 (13.5)
HYDRAULICS	
TYPE	POWER ASSISTED HYDROSTATIC
TOTAL HYDRAULIC FLOW (POWER STEERING+IMPLEMENT)	7.4 (3.1+4.3) / 28.1 (11.7+16.4)
3-POINT HITCH	CAT I
REAR REMOTE VALVE	OPTIONAL (UP TO 1)
3POINT HITCH LIFT CAPACITY @24" BEHIND LIFT POINT	974 (442)
ELECTRICAL	
BATTERY	12 V, 500 CCA
ALTERNATOR	12 V, 60 A
DIMENSIONS	
OVERALL LENGTH IN(MM)	120.7 (3,066)
OVERALL WIDTH IN(MM)	44.2 (1,124)
OVERALL HEIGHT IN(MM)	87.2 (2,216)
WHEELBASE IN(MM)	59.1 (1,502)
MINIMUM GROUND CLEARANCE IN(MM)	12.4 (315)
TURNING RADIUS	46°
WEIGHT LBS(KG)	1,829 (830)
WHEELS & TIRES	
IND (FRONT)	23X8.50-12
IND (REAR)	12-X16.5
LOADER MODEL	BBL200
STANDARD BUCKET SIZE (IN)	50"
MAXIMUM LIFT HEIGHT (IN)	88.3"
DIG DEPTH (IN)	4.2"
LIFT CAPACITY TO FULL HEIGHT AT PIVOT PIN (LBS)	1314
BREAKOUT FORCE (LBS)	1,960
SHIPPING WEIGHT (LBS)	570
BACKHOE MODEL	BBH200
STANDARD BUCKET SIZE (IN)	12"
TYPE	SUBFRAME-MOUNTED, QUICK ATTACH
MAXIMUM DIG DEPTH (IN)	76"
DIG FORCE BUCKET (LBS)	2,050
SHIPPING WEIGHT (LBS)	827



SPECIFICATIONS SUBJECT TO CHANGE

YOUR EXCLUSIVE DEALER: